

## OXYGEN/ACETYLENE GAS SAVER 100SA

- A practical add-on for your gas welding equipment, for oxygen/acetylene torch systems only.
- **How it works:** A double shutoff valve with an external pilot flame designed for quick shut-off and easy restart of your welding torch. The torch flame is automatically extinguished and the gas flow discounted by placing your torch handle on the conveniently located hanger hook. To re-ignite the working flame on torch, lift torch from the hook and wand up the torch tip form under the pilot flame to ignite. The gas saver allows you to safely set down your torch down while adjusting panels and quickly re-light without having to adjust gas flows again
- Come with "B" type hose inlet connectors, (2) pr of 1/4" size barbed connectors of Oxy/Acetylene hoses, bracket kit to allow mounting on welding table or cart
- Save up to 30% of your normal tank consumption by installing a saver today!
- Weight: 3.2 lbs



## DISPOSABLE RESPIRATORS ST-2400N95

- Moldex design; Cool, comfortable, collapse-resistant
- Features Ventex valve that allows hot air out, improves breathing
- For removable of nuisance organic vapors; excellent for welding
- .8 oz.



## WELDING & SOLDERING REPLACEMENT HOSES HW23-12A (12', "A" TYPE INLET CONNECTORS) HW23-12B (12', "B" TYPE INLET CONNECTORS) HW23-25A (25', "A", TYPE INLET CONNECTORS) HW23-25B (25', "B" TYPE INLET CONNECTORS)

- Rubber grade R, color coded, 3/16" I.D
- We can do special lengths & combinations of inlet fitting connectors
- Weight: 1.8 lbs (12'), 3.7 lbs (25')



## GAS WELDING CUP GOGGLES WG6G

- Safe & effective cup style gas welding goggles (meets ANSI Z87-1 standards)
- #5 shade, blue colored, glass lenses (not effective on aluminum welding)
- Weight: .60 lbs



**Aluminum Gas Welding Goggles also available, DT-ALGAS**

## WELDING/GRINDING SAFETY FLIP-UP FACE PROTECTOR SHIELD

**DT-H10C**

(GRINDING/SANDING CLEAR SHIELD & HEADGEAR ASSEMBLY)

**DT-H10-5**

(#5 SHADE: WELDING GRADE SHIELD & HEADGEAR ASSEMBLY)

- Headgear has precision ratchet head size adjuster, 5-position pin lock crown strap. Crown extension adds additional protection for the top of the head from higher temperatures, falling debris and weld splatter
- Offered in clear or #5 shaded for welding shields: .080 H.D thickness-9" x 14.5" coverage
- Weight: 2 lbs



Accessories:

Replacement headgear only: #H10

Replacement window shields: # HC-Clear, #HS- #5 Shaded

## QUICK CONNECTORS-GAS WELDING

- Sold in pairs, built-in check valves prevent reverse flow of gas
- Color coded for safe and easy identification of oxygen & fuel sources
- Click in & Click out design-prior to disconnection, gas must be shut off at regulator
- Pressure tight connections-Max. Working pressure: 29 PSI for fuel gases, 145 PSI oxygen

## HOSE TO HOSE

**MODEL NO: QC-HHPR-A**

"A" style fitting connection (3/8"-24 RH (Oxygen); LH (Fuel))

**MODEL NO: QC-HHPR-B**

"B" style fitting connection (9/16"-18 RH (Oxygen); LH (Fuel))



## HOSE TO TORCH

**MODEL NO: QC-HTPR-B**

"B" style fitting connection (9/16"-18 RH (Oxygen); LH (Fuel))



## REGULATOR TO HOSE

**MODEL NO: QC-RHPR-A**

"A" style fitting connection (3/8"-24 RH (Oxygen); LH (Fuel))

**MODEL NO: QC-RHPR-B**

"B" style fitting connection (9/16"-18 RH (Oxygen); LH (Fuel))

