

# Punch- Flare- Punch/Flare Dies MA0 Series: (Individual sizes)

Punch & Flare tools by size: 1"-1 1/4"-1 1/2"-1 3/4"-2"-2 1/2"-2 5/8"-3" diameters. Precision ground surfaces and cutting edges. These punch & flare tools can be used in three ways: Punch only-punch & flare-flare existing holes. No need to use holes saws any longer, get a uniform, burr free hole. Us the flare option to strengthen and/or lighten a panel. Capacity 16 gauge mild steel, (prepunching hole for the larger diameter versus max. gauge thickness is recommended) Instructions & extra high tensile draw bolt included with each punch & flare tool. **Weight (lbs)** 

3.50



## Punch-Flare 8pc Set MA0484

Punch & Flare tool set of 8 sizes: 1"-1 1/4"-1 1/2"-1 3/4"-2"-2 1/2"-2 5/8"-3" diameter. Precision ground surfaces and cutting edges. These punch & flare tools can be used in three ways: Punch only-punch & flare-flare existing holes. No need to use holes saws any longer, get a uniform, burr free hole. Us the flare option to strengthen and/or lighten a panel. Capacity 16 gauge mild steel, (pre-punching hole for the larger diameter versus max. gauge thickness is recommended) Instructions & extra high tensile draw bolt included with each punch & flare tool.

Weight (lbs) 38.50



## EZ-Bend 90 Tubing Bender-10 ton MA01HP- Hand pump/ MA01FP- Foot pump

Makes smooth wrinkle-free bends in a variety of tubing and pipe. Bending capacity .049 to .180 wall electric weld, d.o.m, & chrome moly tubing (some restrictions tubing diameter versus radius of bend may apply). Utilizes a 10 ton power pump and is offered in a manual pump version (MA01HP) and air/hydraulic foot pump (MA01FP). Range of dies radius and sizes are offered for the bender: 4" die radius ¾"-1"-1-1 1/8"-1 ¼"tubing & ½"& ¾" pipe, 5" die radius ¾"-7/8"-1"-1- 1/8"-1 ¼" tubing, 6" die radius 1 3/8"-1 ½"-1 5/8"-1 ¾" tubing & 1 ¼" -1 ½"pipe, 7" die radius 1 ½"-1 5/8"-1 ¾" tubing & 1 ¼" -1 ½"pipe, 7" die radius 1 ½"-1 5/8"-1 ¾" tubing. Bender requires 6" x 6.5" of bench space. All dies are cast, machined and heat treated. Includes: 4 standard dies, "How to" instructional video, "Bend-It" computer software bending program. Made in USA.

Weight (lbs)

77.00



## "Little Bull" Tubing Bender-Manual DT-LB

E-Z Bend "Little Bull" tubing bender, for its size the strongest, most versatile, and compact. All welded construction (1" x 2" steel frame). Capacity: (steel) Round tubing (3/8" to 1"), square tubing (3/8" to 1"), schedule 40 pipe (3/8" to 1"), flat stock up to 1 1/2" X 1/4'), and solid, round, and square to 3/4'. Comes with (1) *one die of your choice*. (16 styles offered, quick link here to dies offered). Made in USA. Bender will need to be mounted to a floor mounted column or could be held in a bench vise.

Weight (lbs) 26.00



# Adjustable Replication Spline SW3: 37" long, SW6: 67" long

DTSW series adjustable splines can effectively capture a body panel shape and lock in the form for use in the layout of a buck, wire form or template. It can be and effective form checker also. Offered in two lengths: 37" & 67" with a series of locking points that allow you to lie on the panel and lock in the detail. The spline face is .035 thick spring steel at 1 1/4" width allowing it to replicate infinite panel details. Superior tool, heavy-duty construction for accuracy and years of service.

#### Weight (lbs)

4.80



## Build Pro Precision Fixture Welding Tables TM54738: 4' X 3' size, TM57838: 6 ½' X 3' size

BuildPro™ modular fixturing welding tables. Allows easy setup and tear down for the welding job at hand. Save time and money and improve quality by holding, positioning, and locating quickly a wide variety of projects with welding table add-on clamps and components. Tables are offered in two sizes: TM54738 (4' x 3'),(3) different table heights: 36",30",24") & TM57838 (6 1/2' X 3'), (3) different table heights: 36", 30", and 24"). Each table has precision ground steel surface plates, CNC machined 5/8' holes in a 2" grid pattern. Surface plates can be reconfigured to extend the width of the table for larger projects. 1 3/4" spaced surface plates add additional flexibility and access for clamping and components. Heavy duty legs with leveling feet ensure proper leveling even on uneven surfaces. Heavy duty 4 beam support base provides up to 4,400 lbs surface plate table capacity. Surface plates are a robust 5/8" thick. Must ship motor freight collect. Please check out all the optional clamps and component accessories offered to make fixturing most any project possible. Our ecommerce pages have downloadable catalog with all accessories offered.

#### Weight (lbs)

680.00 (TM54738) 900.00 (TM57838)



## 3 ½" Jumbo Bossing Mallet-plastic DBM04D

3 1/2" diameter Jumbo Bossing Mallet, extended reach: 8" head length with 3" radius large end and 1 1/4" radius small end. Latest addition to our jumbo series providing additional roughing capability with this 2.3lb mallet. May not be your day to day go to mallet but like our 3 1/2" wood mallet it can be very useful when you have a larger panel and several inches of depth to create.

#### Weight (lbs)

4.40



## 1 ½" Barrel/Bossing Mallet-plastic DPBRMO

Newest addition to our "Redheads" line of UHMW plastic barrel/bossing mallets. 1 1/2" diameter head x 7" extra long OAL head and with our Dagger Tools standard 14" OAL handle. 7 oz. weight. One side has a 1 1/2" radius bossing head and one side flat with large edge relief. Perfect for edge lipping (included with our LP1 lipping tool) of a panel, raising damaged body panel while off the car on a leather bag, detail forming in hard to reach areas and what a great all around non-marring assembly tool for all types of engine/body work! Weight (lbs)

1.20



## Air Punch & Flange Tool T851

Heavy Duty Air Punch & Flange Tool. Allows you to flange/joggle a panel edge to allow for flush fitting or butting of multiple panels. The 3/16" punch allows you to quickly punch sheets to fill weld. 14 gauge mild steel capacity @ 90PSI inlet air pressure setting. Head swivels 360° of improved access. Very low air consumption: 2.9 CFM per cycle so even the smallest air compressor will power this tool. 9 3/4" O.A.L. Replacement parts available not a throw away!

#### Weight (lbs)

3.90



### Air Speed Hacksaw

#### T125

The "Original" Air Speed Hacksaw. Pistol grip design for comfort and control. Front guard rotates 360° of easy access for most applications. 2.200 stokes per minute with a 1/4" to 1 1/4" adjustable stroke. 16 gauge mild steel capacity. Cast housing construction. Can use standard hack saw blades or you can purchase in dozen packs our V5xx series blades. 6 cfm of air consumption at 90 PSI inlet air pressure. Replacement parts available not a throw away!

#### Weight (lbs)

4.00



### Reversible Air Drill

#### T408

2.90

3/8" chuck capacity. Reversible Angle Drill. 1500 RPM, .33 HP motor, compact low profile angle head design. HD ball and needle bearing gear construction. Planetary gear case for increased drilling torque. Lever throttle-teasing control. One-hand quick reverse lever. Get into to the tight frame and body areas for drilling, reaming, hole saw cutters ect.... 4 cfm air consumption at 90 PSI inlet pressure. Replacement parts available not a throw away! Weight (lbs)



## Pneumatic Turboshear TSHD1A

Pneumatic Heavy Duty Turboshear for sheet metal cutting. 2600 RPM, 4 CFM air requirement, 18ga. mild steel capacity, Cuts straight and to the left with a burr free clean edge. Ideal for sheet metal prep and on the car body section removal. Offset jaw opening allows greater access, handles tight curve patterns, square corners, and mild profiles. Blind cuts require a 1" starting hole. Quick change replacement blades offered: <a href="ISHDRB">ISHDRB</a>

#### Weight (lbs)

2.50



## Door Skin Zipper Tool **21890**

Steck Skin Zipper Tool for installing door skins. Simple 2-step process allows seam closure while limiting skin distortion. One step pre-forms the skin edge to approx. 45° and the second step pre-forms closure. Use with a .401 shank air hammer or rivet gun. Instructional video included.

Weight (lbs) 3.00



## Disposable Deburring Tool DBU05

Disposable Burr, this is a non-replaceable/disposable heavy duty blade for steel or aluminum material. Pocket clip included. 5 1/2" O.A.L

Weight (lbs) 0.30



# .401 Power Forming Driver DT10-RGF

Power forming driver with .401 parker taper shank (use in any air hammer or rivet gun) 5/8" diameter with 1 1/2" useable length over spring lock flat faced brass forming nose with small edge relief. Can be used effectively with leather shot bag to shape panels. Brass head can easily reshape for special applications. Can also be use to turn up edges on panels while limiting surface damage.

Weight (lbs) 0.40



### V-Pad Add-on XFA2

Add a V-Pad (Pipe jaw) Clamp to our UF & UG series 4-1 clamps or PGA20 & PGA20X adjustable long reach locking c-clamps. Has a wire form that can be removed and reinserted quickly to allow pipe or round stock clamping. (these V-Pads can be used without removal on flat stock) (1 pad per package)

Weight (lbs)