

New Tool Additions



Master DeBurring Kit

DBUO-Kit

Master Deburring Tool Kit will allow you to handle any deburring project in most metals.

Includes a double edge deburring tool (DBU03) for work both sides of a sheet safely, adjustable reach style quick-release handle (DBU08) that has keyway deburring head on shaft, 1/2" body countersink head and a 3/4" head and adjustable shaft, internal scraper head with shaft and swivel B series blade holder, quick-change design plus and assortment of 6 blades.

Storage case included.

Weight (lbs)

3.20



Adjustable Blade DeBurring Handle Assembly

DBU08

Adjustable Burr Handle, same unit that is included in our DBUO-KIT. Has a quick-change blade chuck, includes (1) ea B-10 blade & (1) ea B-20 blade. Telescope blade holder from 1/2" to 5". Storage in handle for additional blades.

Weight (lbs)

0.90



Adjustable Trammel Points

DT-R18: 7-18" range

DT-R42: 12-42" range

Adjustable Beam Trammel Points, offered in (2) sizes DT-R18 (7" to 18" radius) DT-R42 (12" to 42" radius).

All steel construction, spring steel handle.

Handy handle serves two purposes: (1) by compressing the handle allows the trammel arms to be precisely set, (2) handle allows more uniform flow in use for accurate line placement. Tips can be re-sharpened or replacement tips are offered.

Weight (lbs)

1.50



Adjustable Sheet Metal Scribe

DL25

Adjustable Sheet Metal Scribe. Scribe 1/4"-12 1/2" depth or at any radius or arc from an edge. This is perfect for more detailed layout of a surface than our standard edge scribes. Uses a common screw metal screw, which is replaceable as the scribe point.

Weight (lbs)

1.50

New Tool Additions



90 degree Offset Hand Snips

P6900R: straight & left hand (Red)

P6900L: straight & right hand (green)

Unique 90 degree offset aviation snip blade design; improves access and comfort in some trimming applications. Forged steel blade design. 18 gauge cap. with a 1 1/4" min radius of cut. Cuts left & straight or right & straight. Midwest Snip brand.

Weight (lbs)

1.50



Heavy-Duty Offset Hand Snips

M2006: straight & left hand (red)

M2007: straight & right hand (green)

Malco Heavy-Duty offset blade hand snips. 16 gauge, which has one the highest mild steel cutting capacities offered in a hand shear. Newly developed ergo handles allow for added comfort and increase output. Spring assist return reduces fatigue. M2006 (red) cuts left & straight, M2007 (green) cuts right & straight.

Weight (lbs)

2.00



Single Blade Fluting Pliers

SC1

Single blade fluting/crimping pliers. Hardened steel blades and compound leverage handles. 19 gauge capacity. Fluting allows a quick method of shrinking metal to conform to a very tight radius contour. Especially when you are working a inside area of a panel and the metal has to shrink rapidly, yet won't be seen. Door skin corner for example.

Weight (lbs)

2.00



Hole Cutter

HC1

The "original" Malco Hole Cutter. The perfect solution for cutting from 2-12" diameter holes in sheet metal. 19 gauge capacity and for cutting instrument panel holes cleanly and accurately. You drill a pilot hole to anchor the pivot pin adjust to the desired diameter, a cordless drill/pneumatic drill on the drill shaft and penetrate the surface and the special spiral flute design cutter allows a quick finish cut. Replacement bits ([HC-repbit](#)) are available. A larger size unit HC2 2-20" diameter hole that can be special ordered.

Weight (lbs)

2.50

New Tool Additions



**Metal Shrinker/Stretcher-Edge type
SS10**

5/8" depth. Produce curves up to 3" radius. For angles and flat sheet in mild steel (up to 18ga.) & Aluminum (up to 16ga). Includes both shrinking & stretching jaws. Has bottom threaded holes for mounting to bench or stand alone table. Imported

Weight (lbs)
15.00



**Powered Bead Roller
BR23**

23" throat depth, Power Bead Roller. 1/3 HP motor (110V voltage), single speed (18 RPM): forward/reverse, floor mount foot control. 18 gauge steel capacity. Steel yoke construction, adjustable stop fence. Includes floor stand, (3) different size step & bead dies, (1) shearing die. Imported. **Must ship Motor Freight.**

Weight (lbs)
168.00



**BR6 Bead Roller-Stand only
BR6-Stand**

BR6 Bead Roller Stand only. Add a floor stand to your BR6 bead roller and provide additional access.

Weight (lbs)
36.00



**Tipping Wheel Set
DT-TP02**

2pc a tipping wheel set. Tipping is one of the few ways to turn an edge in a compound shaped panel when a powered machine method is not available. Works just like a traditional beading die, by stretching a very small surface and allowing the surface to turn up to 90 degrees after several passes at slightly greater pressure settings. Tipping wheel is 2 1/2" in diameter with a .50 radius working edge and has back taper surface to allow sheet clearance. Has a .855 ID bore with a twin set screw lock to fit most bead rollers shafts. Bottom wheel is steel (UHMW plastic version offered also...DT-TP02P) 2" diameter X 2" length with a .855 bore ID. Both top and bottom is heat treated to 30/34 Rockwell C for wear resistance. Instructions included.

Weight (lbs)
4.00

New Tool Additions



**MagTab Bracket & Tab Positioner
MFT-10**

MagTab magnetic tab location bracket holder. Makes welding on tabs and brackets a breeze. Features a flexible design that allows user to position MagTab on either round or flat surfaces. The magnetic tab positioned base is adjustable (offset) to allow tabs/brackets to be positioned in many ways.

Weight (lbs)
0.90



**Mini Oxy/Fuel Torch Handle
114AG: Handle/check valves only
114TAG: Handle/check valves & 00 tip**

Lightweight design Mini Oxy/Fuel torch handle. 6" O.A.L./ 7" O.A.L length with check valves installed (included). A comfort style body design at .870 diameters. Small mixing chamber that will adjust in the 3.5 P.S.I range when used with low pressure oxy/fuel regulators. Uses Victor J-28 series style torch tip types as well as our 171W series tips used on our other style mini torch handle. Uses "A" series hose connectors. Precision cut control seats with needle valves for extended life and flame adjustment. Can be used to weld all alloys, very well suited for thin gauge sheet welding. Oxy/fuel welding provides ductility of weld for re-shape ability. Is offered in kit form as #114TAG with 00 tip, handle & check valves. This is the torch we currently include in our welding kits DT-GW1000G & DT-1000DLXG kits.

Weight (lbs)
2.00



**Oxygen Low Pressure Regulator
DT-11X**

Low-pressure, single stage, Oxygen regulator 0-100 adjustment range. UL listed comes with CGA 540 tank inlet mount. Has type "A" hose outlet fittings only. Offered as a option are Type "A" hose to Type "B" hose connectors. Brass construction with precision diaphragm for accurate pressure flow adjustment. USA made. Regulator is standard in our DT-GW1000G & DT-GW1000DLXG master kits. 3-year warranty

Weight (lbs)
4.00



**Acetylene Low Pressure Regulator
DT-52A**

Low-pressure, single stage, Acetylene regulator 0-30 P.S.I adjustment range. UL listed comes with CGA 510 tank inlet mount (special order with CGA 520 or CGA 300 tanks mounts at no additional cost). Has type "A" hose outlet fittings only. Offered as a option are Type "A" hose to Type "B" hose connectors (please inquire). Brass construction with precision diaphragm for accurate pressure flow adjustment. Made in USA. Regulator is standard in our DT-GW1000G & DT-GW1000DLXG master kits. 3 year warranty

Weight (lbs)
4.50